

	Model Name Surface Colour	Thickness (mm) (inch)	Compressibility	Heatset		Coldset	Sheetfed/Packaging						Metal	Image Reproductively		Paper Release	Sticky Back	Comment
				Coat Paper	Rough Paper		Thick	Thin	Varnish	UV	Perfector	Small offset		Solid	Dot			
Sheetfed	FIT 10 Plus	1.68/1.95 0.067/0.077	Semi Soft	—	—	—	○	○	—	—	○	—	○	○	◎	◎	—	Hi Quality Sheetfed. High-end printing.
	FS-55 Plus	1.68/1.95 0.067/0.077	Semi Hard	—	—	—	○	○	—	—	○	○	○	○	○	○	—	General Sheetfed. Higher color, good smash recovery.
	FS-70	1.95 0.077	Semi Hard	—	—	—	◎	○	—	○	—	—	◎	○	○	○	—	Packaging & 3pc Metal Deco Hybrid type
	FIT Metal	1.95 0.077	Hard	—	—	—	○	○	—	—	○	◎	◎	◎	○	◎	—	3pc Metal Deco Best solid printing
	FS-60	1.95 0.077	Hard	—	—	—	○	○	—	—	○	◎	◎	◎	○	◎	—	Small format press
UV	FIT UV Plus	1.68/1.95 0.067/0.077	Semi Soft	—	—	—	○	◎	—	◎	◎	○	○	○	◎	◎	—	UV printing only
Heatset Web	FIT Web Plus	1.68/1.95 0.067/0.077	Semi Soft	◎	◎	—	—	◎	—	—	—	—	—	○	◎	◎	—	Heatset on Rougher Paper
Newspaper	FIT News Plus	2.1	Semi Soft	—	—	◎	—	—	—	—	—	—	—	◎	○	◎	—	General Newspaper Printing No Pack
Business Form	FIT Form	0.95/1.05 0.037/0.041	Semi Soft	—	—	—	—	—	◎	○	—	—	—	○	◎	—	○	Business Form, Envelope Printing. Hybrid, Sticky back type.
Varnish	FIT COAT (FP-75)	1.68/1.95 0.067/0.077	Semi Soft	—	—	—	—	—	◎	—	—	—	—	—	○	—	—	Stripping blanket for coating



FUJIKURA RUBBER LTD.
藤倉ゴム工業株式会社

TOC Ariake East Tower 10F, 3-5-7, Ariake, Koto, Tokyo, Japan 135-0063

TEL : +81 (3) 3527 8485 FAX : +81 (3) 3527 8520 E mail : info@fujikuragraphics.com

www.fujikuragraphics.com

FUJIKURA GRAPHICS obtained ISO 14001 Certification for environmental management system, and ISO 9001 Quality System Certification.

The content described in this catalog is the one as of January, 2016. The specification and the appearance of each product might change without a previous notice for the improvement.